

Sealaqua

Polyurethane floor seal



Water based polyurethane & acrylic floor seal for use on internal wood & concrete surfaces.

Provides a protective barrier to make the floor easier to clean & maintain.

Produces a durable, slip resistant silk finish.

- Quick drying, which allows a faster application, can be recoated within 2 hours.
- Non-flammable & low odour.
- Suitable for medium traffic areas.
- Coverage per 5 litre - approximately 30 - 40sq. metres for 2 coats.

FLOOR SEALING:

Ensure floor is clean, dry, wax free & neutral.
Use undiluted. Apply a thin even coat with a seal applicator or clean soft brush.
Allow floor to dry between 1 - 2 hours. Apply a second coat & allow to dry.

If the floor is porous further coats maybe necessary.


Drying times can vary depending on ventilation, temperature & humidity.

Sanding in-between coats is not necessary but a light sand with a medium grade floor pad will help key the surface, especially if a third or fourth coat is applied.

After the final coat, leave for a minimum of 12 hours before subjecting to light traffic, and a minimum of 5 days before a maintenance programme is implemented.

RELATED ITEMS:

- Superseal™ - Solvent based polyurethane floor seal.
- Floor & Carpet Care Guide.



5l

Order Code: A025EEV2

Pack: 2 x 5 litre (11.08 kg)

Pallet: 60 Packs

PRODUCT INFORMATION:

Appearance: Opaque white liquid
Odour: Characteristic
pH - undiluted: 8.5
Shelf life: 3 years

COMPOSITION:

Contains a blend of aliphatic polyurethane dispersion & acrylic emulsion.

BIODEGRADABILITY:

All surfactants used in Evans Vanodine products comply with the current European Regulations concerning biodegradability & protection of the environment.

QUALITY ASSURANCE:

This product is manufactured in the U.K. by EVANS VANODINE INTERNATIONAL PLC under an ISO 9001 Quality Management System Cert. No. FM 09535 and an ISO 14001 Environmental Management System Cert. No. EMS 506072 registered by the British Standards Institution.

REVISION DATE:

12/02/18



Evans Vanodine International plc

Brierley Road, Walton Summit, Preston, PR5 8AH, UK
www.evansvanodine.co.uk | Tel: +44 (0)1772 322200 | Fax: +44 (0)1772 626000



ISO 9001
Quality Management

ISO 14001
Environmental Management

